



Piper PA28R-201T Turbo Arrow III,
Piper PA28RT-201T Turbo Arrow IV
With TSIO-360-F, -FB engine



Basic Kit:

- Part Number:** C3F00111STP
- 1 3-Bladed Propeller:** PHC-C3YF-1RF/F7663-4T
- 1 Polished Spinner:** C-3570-P
- 1 STC Document Set:** SA01024CH

Aircraft Serial and registration numbers required when ordering
All Prices FOB Hartzell Propeller Inc.
Prices do not include Ohio State Sales Tax
Installation and Dynamic Balancing available at an additional charge

Telephone: (937) 778-5726 Option 2 / (800) 942-7767 Option 2
Internet: www.hartzellprop.com

Fax: (937) 778-4215
Email: topprop@hartzellprop.com

TOP
PROP
PERFORMANCE
CONVERSIONS



PIPER TURBO ARROW

Applicable Models: PA-28R-201T, PA-28RT-201T

Specifications: 74 inch diameter 3-bladed aluminum hub propeller
 2400 hour / 6 year TBO
 74 pounds (propeller and spinner)
 Diameter reduction allowable to 72 inches

Replaces: Hartzell BHC-C2YF-1()F/F8459A-8R - 76 inch dia. 2-bladed prop
 Diameter reduction allowable to 75 inches
 2000 hour / 5 year TBO
 54 pounds (propeller and spinner)
 Placard - "Avoid continuous ground operation 1700-2100 RPM in cross/tail winds over 10 kts."
 Placard - "Avoid continuous operation 2000-2200 RPM above 32" manifold pressure."

Advantages: Increased ground clearance
 Lower noise
 Eliminates placard
 Improved appearance
 Greater diameter repair